

Introducing ThermoThin Hook-Up Wire

with high temperature performance in an ultra-thin wire



**Smaller
and
Lighter
than PTFE**

Temperature Range: -150°C to +300°C

Conductor Size: 36 AWG to 16 AWG

Insulation: ECA Fluoropolymer

Conductor Type: Nickel Plated Copper

Availability: 100 and 1000 ft., with the ability to run in long continuous lengths

Insulation Tints:

Black, White, Blue, Red, Orange, Green, Yellow, Brown, Violet, Slate*

*Due to unique insulation compound, color is opaque and conductors are visible



AlphaWire


Cables you trust. Service you deserve.

Sample the Performance Today!



ThermoThin

Part Number 2928, 28 AWG Stranding 7/36 (Conductor OD is 0.015") Insulation Thickness 0.004", OD 0.023" 600V. All items have CE listing except UL AWM 11540 (30 AWG and larger)



PTFE

Part Number 5852, 28 AWG Stranding 7/36 (Conductor OD is 0.015") Insulation Thickness 0.010", OD 0.035" 600V, UL AWM 1213 and MIL-W-16878/4 (Type E)

ThermoThin

- High & Low Temp
- Smaller & Lighter
- In Stock
- Chemical/UV Resistant
- Water Resistant
- Abrasion Resistant



AlphaWire

Cables you trust. Service you deserve.