

Harsh Industrial Environments

Industrial Ethernet Patch Cords: Cat 5e Stranded Unshielded



Product Description	EtherNet/IP, Stranded/Unshielded high-flex, double-ended patch cord, M12 male to male straight, 4-pin, D-coding, 24 AWG TPE cable, oil resistance, 2-Pair with teal jacket.	WireXpress Part #	IP Rating	Length
		L3-2M-CAT5-STR	IP68	2 Meter
		L3-5M-CAT5-STR	IP68	5 Meter
		L3-10M-CAT5-STR	IP67	10 Meter

Ethernet/IP Double-Ended Patch Cord: CAT 5e, High-Flex, 2 Pair, Stranded/Unshielded, 24 AWG, TPE Jacket	
Degree of protection	IP68
Temperature	-40°C to 75°C
Mechanical	
M12 and M12 Receptacle	
Molded body	PUR, black
Coupling nut	Metal
Contacts	Gold/silver plated
Insert	PUR, black
Electrical	
Current rating	4A
Voltage rating	250V
Performance	CAT5e

Cable Specifications	
Cable jacket	TPE
Color	Teal
Overall diameter	0.275 in.
Conductor	Stranded copper
Temperature	Operating: -40°C to 75°C / Installation: -25°C to 75°C
Flame test	UL: CMR / CSA: CMG