

Light Industrial Environments Industrial Ethernet Cable: Cat 5e 24-4 Pair Stranded Shielded



L2-5E-STR-SHLD-02	4 PR 24 AWG stranded (7x32) bare copper conductors, polyolefin insulation, polyester separator, foil- shield (100% coverage), drain wire, industrial grade sunlight- and oil-resistant PVC jacket.
--------------------------	--

Physical Characteristics (Overall)	
Conductor	
# Pairs	4
AWG	24
Stranding	7x32
Material	BC - Bare Copper
Total # of Conductors	8
Insulation	
Material	PO - Polyolefin
Wall Thickness	0.01 in.
Diameter	0.04 in.
Outer Shield	
Type	Tape
Material	Aluminum Foil-Polyester Tape
Coverage	100%
Drain Wire AWG	24
Drain Wire Stranding	7x32
Drain Wire Conductor Material	TC - Tinned Copper

Outer Jacket	
Material	Industrial Grade PVC - Polyvinyl Chloride
Nom. Wall Thick.	0.030 in.
Outer Jacket Rip Cord	No
Overall Cable	
Overall Nominal Diameter	0.315 in.
Overall Cabling Separator Material	Polyester
Pair Color Code Chart	
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe and Green
4	White/Brown Stripe and Brown
Mechanical Characteristics (Overall)	
Installation Temperature Range	-25°C To +75°C
Operating Temperature Range	-40°C To +75°C
Bulk Cable Weight	35 lbs/1000 ft.
Max. Recommended Pulling Tension	40 lbs.
Min. Bend Radius/Minor Axis	0.600 in.
Applicable Specifications and Agency Compliance (Overall)	
Applicable Standards & Environmental Programs	
CEC/C(UL) Specification	CMR
EU Directive 2011/65/EU (ROHS II)	Yes
EU Directive 2000/53/EC (ELV)	Yes
EU Directive 2002/95/EC (RoHS)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	8/23/2007
EU Directive 2002/96/EC (WEEE)	Yes
EU Directive 2003/11/EC (BFR)	Yes
CA Prop 65 (CJ for Wire & Cable)	Yes
MII Order #39 (China RoHS)	Yes

Applicable Standards & Environmental Programs (Cont.)	
Other Specification	NEMA WC-63.1 Category 5e Patch, ICEA 661 Category 5 Patch, UL verified to Category 5e
Flame Test	
UL Flame Test	UL1666 Riser
CSA Flame Test	FT4
IEEE Flame Test	1202
Suitability	
Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Sunlight Resistance	Yes
Oil Resistance	Yes
Plenum/Non-Plenum	
Plenum (Y/N)	No