

Light Industrial Environments Power Supplies: 24V 5 A Single Phase



Item #	Product Description
L2-24V-5A-1P	DIN Rail Mount Power Supply, Single Phase, 24 VDC / 5A

Input Circuit		
Rated input voltage U	115 / 230 V AC auto select	
Input voltage range	90-132 V AC, 180-264 V AC / 210-375 V DC	
Frequency range AC	47-63 Hz	
Typical input current	at 115 V AC	2.2 A
	at 230 V AC	0.83 A

Typical power consumption		140 W
Inrush current limiting	at 115 V AC	24 A (max. 5 ms)
	at 230 V AC	48 A (max. 5 ms)
Internal input fuse		3.15 A slow-acting / 250 V AC
Power factor correction (PFC)		yes, passive, 0.7
Indication of Operational States:		
Output voltage	Green LED	OUTPUT OK: V: output voltage OK
	Red LED	OUTPUT LOW: V: output voltage too low
Output Circuit		
Rated output voltage		24 V DC
Tolerance of the output voltage		0...+1 %
Adjustment range of the output voltage		22.5-28.5 V DC
Rated output power		120 W
Rated output current I		5 A
Signaling contact for output voltage OK		solid-state (max. 60 V DC, 0.3 A)
Minimum fuse rating to achieve short-circuit protection		M 60 V DC, 0.3 A fast-acting
Output circuit - No-load, overload and short-circuit behavior:		
Power dissipation		typ. 20 W
Efficiency		typ. 86 %
Duty time		100%
Dimensions (W x H x D)		63.2 x 123.6 x
		123.6 mm
		[2.49 x 4.87 x 4.87 in]

Weight	0.882 kg (2.20 lb)	
Material of housing	Metal	
Mounting	DIN rail (IEC/EN 60715), snap-on mounting without any tool	
Mounting position	horizontal	
Degree of protection housing / terminals	IP 20 / IP20	
Electrical connection - input circuit / output circuit:		
Wire size fine-strand with wire end ferrule	fine-strand with wire end ferrule	0.2-4 mm ² (24-11 AWG)
	fine-strand without wire end ferrule	0.2-6 mm ² (24-10 AWG)
	rigid	
Stripping length	8 mm (0.31 in)	
Environmental Data		
Ambient temperature range	operation	-35...+70 °C
	rated load	-35...+60 °C
	storage	-40...+85 °C
Damp heat (cyclic)	(IEC/EN 60068-2-30)	95 % without condensation
Shock (half-sine)	(IEC/EN 60068-2-27)	15 G, 11 ms, 3 axes, 6 faces, 3 times for each face
Vibration (sinusoidal)	(IEC/EN 60068-2-6)	10-500 Hz, 2 G, along X, Y, Z each axis, 60 min. for each axis
Standards		
Product standard	EN 61204-3	
Low Voltage Directive	2006/95/EC	
EMC directive	2004/108/EC	
RoHS directive	2002/95/EC	
Electrical safety	EN 60950-1, UL 60950-1, UL 508, EN 61558-1, EN 61558-2-17; EN 60204-1	

Electromagnetic Compatibility		
Interference immunity to:		IEC/EN 61000-6-2
Electrostatic discharge	IEC/EN 61000-4-2	Level 4 (air discharge 15 kV / contact discharge 8 kV)
Radiated, radio-frequency, electromagnetic field IEC/EN	IEC/EN 61000-4-3	Level 3 (10 V/m)
Electrical fast transient/burst	IEC/EN 61000-4-4	Level 4 (4 kV / 5 kHz)
Surge	IEC/EN 61000-4-5	L-L Level 3 (2 kV) / L-PE Level 4 (4 kV)
Conducted disturbances, induced by radio-frequency fields	IEC/EN 61000-4-6	Level 3 (10 Vrms)
Power frequency magnetic fields	IEC/EN 61000-4-6	Level 4 (30 A/m)
Voltage dips, short interruptions and voltage variations	IEC/EN 61000-4-6	dip: >95 % 10 ms / >30 % 500 ms interruptions: >95 % 5000 ms
Interference emission		IEC/EN 61000-6-3
High-frequency radiated	IEC/CISPR 22, EN 55022	Class B
IEC/CISPR 22, EN 55022	IEC/CISPR 22, EN 55022	Class B
Limits for harmonic current emissions		Class D