

## Office Environments Industrial Ethernet Cable: Cat 5e 24-4 Pair Solid UTP White



<b>L1-5E-SOL-UTP-01</b>	CAT5e (200MHz), 4-Pair, U/UTP-Unshielded, Riser-CMR, Premise Horizontal Cable, 24 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Ripcord, White PVC Jacket.
-------------------------	---

Physical Characteristics (Overall)	
<b>Conductor</b>	
<b># Pairs</b>	4
<b>AWG</b>	24
<b>Stranding</b>	Solid
<b>Material</b>	BC - Bare Copper
<b>Total # of Conductors</b>	8
<b>Insulation</b>	
<b>Material</b>	PO - Polyolefin
<b>Outer Shield</b>	
<b>Type</b>	Unshielded
<b>Outer Jacket</b>	
<b>Material</b>	PVC - Polyvinyl Chloride
<b>Nominal Diameter</b>	.190 in.
<b>Outer Jacket Rip Cord</b>	Yes

<b>Pair Color Code Chart</b>	
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown
<b>Mechanical Characteristics (Overall)</b>	
Installation Temperature Range	0°C To +60°C
Operating Temperature Range	-20°C To +60°C
Max. Recommended Pulling Tension	35 lbs.
<b>Applicable Specifications and Agency Compliance (Overall)</b>	
<b>Applicable Standards &amp; Environmental Programs</b>	
NEC/(UL) Specification	CMR
NEC Articles	800
CEC/C(UL) Specification	CMR
Other Standards	ISO/IEC 11801 ed 2.1 (2008) Class D
EU CE Mark	Yes
EU Directive 2011/65/EU (ROHS II)	Yes
EU Directive 2000/53/EC (ELV)	Yes
EU Directive 2002/95/EC (RoHS)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	1/1/2004
EU Directive 2002/96/EC (WEEE)	Yes
EU Directive 2003/11/EC (BFR)	Yes
CA Prop 65 (CJ for Wire & Cable)	Yes
MII Order #39 (China RoHS)	Yes
Telecommunication Standards	Category 5e - TIA 568.C.2
Other Specification	NEMA WC-63.1 Category 5e
<b>Flame Test</b>	
UL Flame Test	UL1666 Vertical Riser
CSA Flame Test	FT4
IEEE Flame Test	1202

Suitability	
Suitability - Indoor	Yes
Suitability - Outdoor	No
Sunlight Resistance	No
Oil Resistance	No
Plenum/Non-Plenum	
Plenum (Y/N)	No