

## Office Environments Industrial Fiber Cable: Plenum 2-Fiber 50.0 OM3



<b>L1-02-FTB-OM3-16P</b>	Tight-Buffered Fiber Cable, Plenum, 2 F, 50.0 $\mu$ m multimode (OM3), Aqua
--------------------------	---

<b>General Specifications</b>	
<b>Environment</b>	Indoor
<b>Application</b>	General Purpose Horizontal, Vertical Riser, Plenum
<b>Cable Type</b>	Tight-Buffered
<b>Product Type</b>	Distribution
<b>Flame Rating</b>	Plenum (OFNP)
<b>Fiber Category</b>	50 $\mu$ m MM (OM3)
<b>Standards</b>	
<b>Approvals and Listings</b>	National Electrical Code® (NEC®) OFNP, CSA FT-6, ICEA S-83-596
<b>Flame Resistance</b>	NFPA 262 (for plenum, riser and general building applications)
<b>Cable Design</b>	
<b>Central Element</b>	Yarn
<b>Fiber Count</b>	2
<b>Tight Buffer Color</b>	Blue, Orange
<b>Tensile Strength Elements and/or Armoring - Layer 1</b>	Dielectric strength members
<b>Outer Jacket Material</b>	Flame-retardant
<b>Outer Jacket Color</b>	Aqua

<b>Temperature Range</b>	
<b>Storage</b>	-40 °C to 70 °C (-40 °F to 158 °F )
<b>Installation</b>	0 °C to 60 °C (32 °F to 140 °F )
<b>Operation</b>	0 °C to 70 °C (32 °F to 158 °F )
<b>Mechanical Characteristics Cable</b>	
<b>Max. Tensile Strength, Short-Term</b>	440 N (100 lbf)
<b>Max. Tensile Strength, Long-Term</b>	132 N (30 lbf)
<b>Weight</b>	21 kg/km (15 lb/1000 ft)
<b>Nominal Outer Diameter</b>	5 mm (0.2 in)
<b>Min. Bend Radius Installation</b>	75 mm (3 in)
<b>Min. Bend Radius Operation</b>	25 mm (1 in)
<b>Optical Characteristics (Cabled)</b>	
<b>Fiber Core Diameter</b>	50 µm
<b>Fiber Category</b>	OM3
<b>Fiber Code</b>	T
<b>Performance Option Code</b>	80
<b>Wavelengths</b>	850 nm / 1300 nm
<b>Maximum Attenuation</b>	2.8 dB/km / 1.0 dB/km
<b>Serial 1 Gigabit Ethernet</b>	1000 m / 600 m
<b>Serial 10 Gigabit Ethernet</b>	300 m / - m
<b>Min. Overfilled Launch (OFL) Bandwidth</b>	1500 MHz*km / 500 MHz*km
<b>Minimum Effective Modal Bandwidth (EMB)</b>	2000 MHz*km / - MHz*km